

# TM45 M

Tubular motor with mechanical limit switch for push-button control with manual override device

Max. torque

15 - 45 Nm

Max speed

12 - 17 rpm

Lifting capacity

28 - 81 Kg



## TECHNICAL SPECIFICATIONS

Model	TM45 15/17 M	TM45 30/17 M	TM45 40/17 M	TM45 45/12 M
Max. torque	15 Nm	30 Nm	40 Nm	45 Nm
Lifting capacity	28 Kg	56 Kg	72 Kg	81 Kg
Max speed	17 rpm	17 rpm	17 rpm	12 rpm
Use frequency	20%	20%	20%	20%
Continuous use time (ROT)	240 s	240 s	240 s	240 s
Power supply voltage	230V~ 50Hz	230V~ 50Hz	230V~ 50Hz	230V~ 50Hz
Max. power	180 W	250 W	300 W	270 W
Max stroke	28	28	28	28
Motor diameter	45 mm	45 mm	45 mm	45 mm
Length with adapter (L)	638 mm	663 mm	663 mm	638 mm
Protection class	IP 44	IP 44	IP 44	IP 44

The term **lifting capacity** refers to the maximum liftable weight using a 60 mm diameter winding tube, including the rolling and friction coefficient.

## DIMENSIONS

