

## 230V Hydraulic operator



Max width of single panel

1,5 - 2 m

Use frequency (cycles/hour)

50



- Ideal for bi-folding doors. Opening and closing through telescopic arm.
- In case of power cut the release device on the operator makes it possible to open and close the gate manually.
- Anti-crushing guaranteed by a pair of by-pass valves.



**GREENTech**  
system:  
560 + E045 or E145



## DIMENSIONS AND TECHNICAL SPECIFICATIONS

Model	560 CBAC	560 SB
Power supply voltage	220-240V~ 50/60 Hz	220-240V~ 50/60 Hz
Motor	Asynchronous single phase	Asynchronous single phase
Max. power	220 W	220 W
Max expressed force	-	-
Max. torque	320 Nm (*)	320 Nm (*)
Max. angular speed	12,4 °/s (*)	12,4 °/s (*)
Motor-pump unit capacity	1 lpm (*)	1 lpm (*)
Operating ambient temperature	-20 °C ÷ +55 °C	-20 °C ÷ +55 °C
Thermal protection	120°C	120°C
Protection class	IP55	IP55
Type of oil	FAAC HP OIL	FAAC HP OIL
Weight	12 Kg	12 Kg
Dimensions (LxDxH)	480 x 85 x 110 mm	480 x 85 x 110 mm
Electronic equipment	Not included	Not included
Max. leaf width	1,50 m (single panel)	2,00 m (single panel)
Use frequency	50 cycles/hour	50 cycles/hour

(\*) data referred to 230V~ 50Hz.