

230V Hydraulic operator



Door max dimensions (W x H)

3,5 x 3 m (6 x 4 m with
two operators)

Max. door weight

15 Kg/m²

Use frequency (cycles/hour)

60

- Anti-crushing safety device thanks to an hydraulic device.
- A safe long-lasting, powerful and quiet operator.
- Guaranteed door hold when opening, even in strong wind conditions.



GREENTech
system:
580 + E045 or E145



DIMENSIONS AND TECHNICAL SPECIFICATIONS

Model	580 CBAC
Power supply voltage	220-240V~ 50/60 Hz
Motor	Asynchronous single phase
Max. power	220 W
Max. torque	450 Nm (*)
Motor-pump unit capacity	0,75 lpm (*)
Max. angular speed	9°15'/s (*)
Opening time	20
Operating ambient temperature	-20 °C ÷ +55 °C
Thermal protection	120 °C
Protection class	IP55
Type of oil	FAAC HP OIL
Weight	12 Kg
Dimensions (LxDxH)	480 x 96 x 110 mm
Max. door dimension (LxH)	3,50 x 3,00 (**)
Max. door weight	15 Kg/m ²
Electronic equipment	Not included
Use frequency	60 cycles/hour

(*) data referred to 230V~ 50Hz.

(**) For doors with width of over 3,50 m install two operators. An electric lock should be installed for operators without hydraulic locking.