

620 SR

Automatic 230V Barrier



Max beam length

3 m

Opening time

0,8 - 2,2 s

Use frequency

Continuous use



- Hydraulic deceleration and barriers status signalling through traffic management devices.
- Ideal for continuous control of high speed vehicle traffic
- Two channels integrated detector and 11 pre-set logics



DIMENSIONS AND TECHNICAL SPECIFICATIONS

Model	620 SR Standard
Power supply voltage	220-240V~ 50/60 Hz
Motor	Asynchronous single phase
Motor rotation speed	2.800 rpm (*)
Max. power	220 W
Max. torque	0 ÷ 80 Nm (*)
Motor-pump unit capacity	3 lpm (*)
Material type	Steel
Type of treatment	100 micron zinc epoxy galvanisation + polyester painting RAL 2004
Encoder	No - anti-crushing hydraulic safety device
Type of deceleration	Hydraulic and electronic - Adjustable with cams
Type of beam	Rectangular - Round pivoting
Operating ambient temperature	-20°C ÷ +55°C
Thermal protection	130°C
Cooling	With forced air
Protection class	IP44
Weight	80 kg
Type of oil	FAAC HP OIL
Dimensions (LxDxH)	380 x 200 x 1080 mm
Beam max length	3 m
Opening time	0,8 s (90° - 3 m)
Use frequency	100%
Electronic equipment	624BLD incorporated

(*) data referred to 230V~ 50Hz.