

620 TT

Automatic 230V Barrier



Max beam length

2 - 3 m

Opening time

1,4 s

Use frequency

Continuous use



- Hydraulic operator with opening and closing lock
- Ideal for control of heavy but not continuous vehicle traffic
- Patented electronic deceleration
- The barrier statuses can be signalled to the traffic control devices
- Automatic logics, semiautomatic logics, parking logics, condominium and customized logics



DIMENSIONS AND TECHNICAL SPECIFICATIONS

Model	620TT
Power supply voltage	230V- 50 Hz
Motor	Asynchronous single phase
Motor rotation speed	2800 rpm
Max. power	220 W
Max. torque	0 ÷ 120 Nm
Motor-pump unit capacity	3 lpm
Material type	Steel
Type of treatment	100 micron zinc epoxy galvanisation + polyester painting RAL 2004
Encoder	No - anti-crushing hydraulic safety device
Type of deceleration	Electronic - Adjustable with cams
Type of beam	Rectangular - Round - Round pivoting
Operating ambient temperature	-20°C ÷ +55°C
Thermal protection	120°C
Cooling	With forced air
Protection class	IP44
Weight	73 Kg
Type of oil	FAAC HP OIL
Dimensions (LxDxH)	350 x 170 x 1080 mm
Beam max length	3 m
Opening time	1,4 s (90° - 3 m)
Use frequency	100%
Electronic equipment	624BLD incorporated