



770N 230V

Underground electromechanical operator



Max width single leaf

2 - 3,5 m

Max weight

500 Kg

Use frequency

S3 - 30%

- Invisible operator
- Access to the operator is possible without removing the leaf
- Manual release with double lever accessible both from inside and outside of the property (Patented)



230V SAFEzone system:
770 230V + E045 or
E145 + SAFEcoder



GREENTech 230V system:
770 230V + E045
or E145



DIMENSIONS AND TECHNICAL SPECIFICATIONS

Model	770N 230V
Power supply voltage	220-240V~ 50/60 Hz
Motor	Asynchronous single phase
Max. power	380 W
Max. torque	330 Nm (*)
Max. angular speed	6 °/s (*)
Max. leaf weight	500 Kg (see graph)
Max. leaf opening angle	110° (140° and 180° with optional kit)
Operating ambient temperature	-20°C ÷ + 55°C
Thermal protection	140°C
Protection class	IP67
Weight	12 Kg (with foundation box 14 Kg)
Use frequency	S3 30%
Max. leaf width	2 m (3,5 m with electric lock)
Dimensions (LxDxH)	360 x 150 x 140 (foundation box 430 x 307,5 x 214) mm
Electronic equipment	Not included

(*) data referred to 230V~ 50Hz.