

J275 F

Fixed traffic bollard



Type of operator

Fixed

Height

600 or 800 mm



- Power supply and wiring not requested
- Simple laying and limited excavation
- Guarantees aesthetic coherency in multiple installations together with retractable bollards.



DIMENSIONS AND TECHNICAL SPECIFICATIONS

Model	J275 F H600	J275 F H800	J275 F H600 Stainless steel	J275 F H800 Stainless steel
Cylinder height from ground	600 mm	800 mm	600 mm	800 mm
Cylinder diameter	275 mm	275 mm	275 mm	275 mm
Cylinder material	Steel S235JR EN 10219 (7mm thick)		Satin-finished AISI 316L (6mm thick)	
Cylinder treatment	Cataphoresis and polyester powder paint, dark grey metallised RAL 7021		Satin finish	
Reflective strip height	55 mm	55 mm	55 mm	55 mm
Standard reflecting strip colour	Orange	Orange	Orange	Orange
Break in resistance	35000 J	35000 J	59000 J	59000 J
Total weight	34 Kg	38 Kg	34 Kg	38 Kg
Walled in pit with cylinder profile (LxWxH)	450 x 450 x 55 mm	450 x 450 x 55 mm	450 x 450 x 55 mm	450 x 450 x 55 mm
Excavation dimensions (LxWxH)	750 x 750 x 150 mm	750 x 750 x 150 mm	750 x 750 x 150 mm	750 x 750 x 150 mm