

S450H

24V Hydraulic operator



Max width single leaf

2 - 3 m

Use frequency

Continuous use

- Hybrid Technology (Hydraulic + 24V).
- Integrated encoder SAFECoder with anti-crushing function and reverse upon obstacle detection.
- Opening and closing mechanical stops included.



24V SAFEzone system:
S450H + E024S or
E124



GREENTech system:
S450H + E124



DIMENSIONS AND TECHNICAL SPECIFICATIONS

Model	S450H CBAC	S450H SB
Power supply voltage	220-240V~ 50/60 Hz	220-240V~ 50/60 Hz
Motor	With brushes 24V	With brushes 24V
Max. power	60 W	60 W
Max expressed force	> 5000 N	> 5000 N
Rod max speed	>25 mm/sec	>25 mm/sec
Rod travel	311 mm	311 mm
Max. leaf opening angle	110°	110°
Operating ambient temperature	-20°C ÷ +55°C	-20°C ÷ +55°C
Protection class	IP55	IP55
Weight	6.5 Kg	6.5 Kg
Use frequency	Continuous use	Continuous use
Max. leaf width	**nt**	3 m
Type of oil	FAAC HP OIL	FAAC HP OIL
Mounting brackets	Rear multi-position bracket to be screwed - front adjustable to be screwed	
Dimensions (LxDxH)	1113 x 85 x 119 mm	1113 x 85 x 119 mm
Electronic equipment	Not included	Not included