

TM58 ER

Tubular motor with electronic limit switch and integrated receiver for remote radio control (433 MHz)

Max. torque

70 - 120 Nm

Max speed

12 rpm

Lifting capacity

80 - 138 Kg



TECHNICAL SPECIFICATIONS

Model	TM58 70/12 ER	TM58 80/12 ER	TM58 100/12 ER	TM58 120/12 ER
Max. torque	70 Nm	80 Nm	100 Nm	120 Nm
Lifting capacity	80 kg	92 Kg	115 Kg	138 Kg
Max speed	12 rpm	12 rpm	12 rpm	12 rpm
Use frequency	20%	20%	20%	20%
Continuous use time (ROT)	240 s	240 s	240 s	240 s
Power supply voltage	230V~ 50Hz	230V~ 50Hz	230V~ 50Hz	230V~ 50Hz
Max. power	310 W	320 W	410 W	450 W
Max stroke	51	51	51	51
Motor diameter	58 mm	58 mm	58 mm	58 mm
Length with adapter (L)	610 mm	610 mm	620 mm	620 mm
Protection class	IP 44	IP 44	IP 44	IP 44

The term **lifting capacity** refers to the maximum liftable weight using a 70 mm diameter winding tube, including the rolling and friction coefficient.

DIMENSIONS

